

Retrofit Turnkey Solution

Consultancy → Engineering → Purchasing → Construction

Clear Responsibility

Open Price of 3rd Party

High Project
Management Efficiency

Dynamic Efficiency
Improvement Suggestions

01



Consultancy & 3D Scanning Survey

- Feasibility Study Report
- Concept Report

02



Equipment Selection & Purchase

- Maker authorizations 30+
- Multiple makers selection
- Open price of equipment

03



Design & Class Review

- High accuracy, ensure minimum onsite modification
- Fast drawing delivery, design on direct 3D modeling
- Average 13 years design experience

04



Material & Fabrication

- Self-own workshop
- Design team in charge of quality control of material and fabrication ensure minimum onsite modification

05



Installation, Commissioning & After-sales Service

- Several yard's representative, such as Beihai, SHG, CUD, ZTHI, Zhoushan Longshan, etc
- Maker Authorizations 30+
- 200+ technicians

06



Supervision & Electrical Retrofit

- Supervisors 30+
- Electric modification: MSBD/AMS/GPS/VRC and other peripheral systems modify, such as Hyundai, JRCs, BEMAC, Taiyo, TERASAKI, Kongsberg, etc.

07



Sea Trial & Training

- Seaman book 50+
- Onboard Sea trial or measurement
- Regular training
- Customized training

► WinKong Marine Engineering Co., Ltd.

About SmartEco

Abundant Retrofit Engineering Experience

Established in
2017

Retrofit & New Projects
1,000+


Cooperated Manufacturers
30+

Design Engineers
30+

• Self-Own Multi-Team Cooperation

- Green decarbonization retrofit team for feasibility Study & Design.
- New energy R&D team for new technology evolution
- Technical & engineering team for installation & electrical modification

• Design Engineer Experience Average 13.8Y



• Work Experience Ratio

WinKong Marine Engineering Co., Ltd.

Platform website: www.marinsmart.pro
Company website: www.winkong.net

Tel: +86 0532 83838072
E-mail: newmkt@winkong.net

Social Media: [@winkongmarine](https://www.instagram.com/winkongmarine)



www.marinsmart.pro



SMARTECO

Green Decarbonization Solutions of Full Life Cycle

- ✓ Package with Ship Energy Efficiency Management for Data Analysis
- ✓ Power System Optimization Solutions
- ✓ Propulsion System Optimization Solutions
- ✓ Hydrodynamic Optimization Solutions
- ✓ Emission Reduction Solutions
- ✓ Alternative Fuel/Energy Supply System Retrofit




Green and Low-Carbon Solutions, Empower Clean Shipping

WinKong Marine Engineering Co., Ltd.

Green Decarbonization Solutions of Full Life Cycle

Based on Energy Efficiency Management (EEM) System



Advantages of EEM

- Approved by class.
- Data acquired automatically, accurate and credible.
- Connected automatically with DNV OVD for verification, generate DCS and MRV reports, providing data support for owner's EU ETS and FuelEU.
- Continuous energy efficiency optimization suggestions.



Provide Multiple Engineering Solutions



Propulsion System Optimization

- Rotor Sailor Retrofit
- ALS(Air lubrication system) Retrofit
- TCCO(Turbo charger cut-out) Modification

Options

Power System Optimization

- Shaft Generator Retrofit
- AMP-Alternative Maritime Power (Shore Power System)
- VFDs Modification
- LED Retrofit
- Electric Power Quality Optimization

Emission Reduction

- OCCS(Onboard carbon capture system) Retrofit
- EGCS Retrofit
- SCR Retrofit
- Ship GHG Comprehensive Solutions

Hydrodynamic Optimization

- High Efficiency Propeller Retrofit/Modification
- PSV(Pre-shrouded vanes) Retrofit
- HVAF(Hub vortex absorbed fins) Retrofit
- PSS Retrofit
- WID Retrofit
- FR Retrofit


Alternative Fuel/Energy Supply System Retrofit

- Methanol Low-flashiont Fuel Supply System (LFSS) Design
- LNG Fuel Gas Supply System (FGSS) Design
- Ammonia Fuel Gas Systems (AFSS) Design

Shaft Generator Retrofit Case

The shaft generator retrofit plan could allow vessel to only run Main Engine and Shaft Generator without running D/G during seagoing, which can improve the energy saving by 3%~8% and upgrade the SEEMP level subject to different vessel types.

3D Modeling Design



Installation Info

- Install between main engine and intermediate bearing.
- After calculating the strength requirement of the intermediate bearing, the strength of the intermediate bearing bush changed from 302kN to 478kN. Load test of shafting.
- The installation was carried out in a Chinese shipyard, the installation period was 25 days (including 5 days of commissioning), and the time in dock was 9 days (with energy saving appendages retrofitting).
- 5 days of peripheral electrification (simultaneous).

Vessel Type	230K Bulk carrier	Class: ABS
Main Engine	MAN B&W 6S80MC-C, MCR 23,280kW	
Shaft Generator	1,400kW	
Content	Before	After
Main engine power	6,900kW	8,230kW
M/E SFOC	174.2g/kWh	172.3g/kWh
M/E daily fuel consumption	28.8t	34.0t
Generator power	1,200kW	0kW
Generator SFOC	242g/kWh	0g/kWh
Daily fuel consumption of generator	7.0t	0t
Daily fuel consumption (M/E+A/E)	35.8t	34.0t
After retrofit Daily fuel savings	1.78t	
Savings on daily fuel costs @\$50 USD/t LSHFO	979USD	
Save maintenance cost @\$USD/d	145.5USD	
Sailing days per year	240	
Annual fuel savings	427.2t	
Annual cost savings	269,880USD	
Fuel saving rate	5.0%	



Hydrodynamic, AMP, VFDs Retrofit Case



Hydrodynamic Optimization

Advantages : ☒ Economic Practicability ☒ High Energy-Saving Efficiency ☒ Compatibility&Adaptability ☒ Technical Maturity

Cases							
PBCF(Propeller Boss Cap Fin)				PSV(Pre-shrouded Vanes)			
	Case Info	Energy saving	ROI (Year)		Case Info	Energy saving	ROI (Year)
	Vessel Type 57K BC	2%	1~2		Vessel Type 180K BC	4.6%	1~2

Alternative Maritime Power

Installation type:

- Container unit type
- Modified original room
- New AMP room



Cable reel modeling design



Cable reel installation



Electrical cabinet installation



System test

VFDs - Modification

General Information			
Type	DWT	Main Engine	M/E MCR
Bulk Carrier	85,000	B&W 6S60ME	9,660kW x 89.0 rpm
VFDs Retrofit Selection			
Equipment	Power(kW)	Quantity(ea)	Modification Plan
Main cooling sea water pump	55	1+1(standby)	1) Add VFD + control panel 1set 2) Add Temp. sensor 3pcs -Main cooling sea water pump outlet -before Sea Water Overboard valve -M/E Cool. F.W. System outlet 3) Add outlet Press. Sensor 1pc
G/E cooling fresh water pump (driven by G/E)	/	1+1(standby)	No need to modify
M/E fresh water cooling pump	18.5	1+1(standby)	No need to modify
Equipment			
Item	Q'ty		
VFD + Control Panel	1set		
Temp. Sensor	3pcs		
Press. Sensor	1pc		
Junction Box	1set		

